



Revision Number: 003.2 Issue date: 02/12/2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Silver Grade Anti-Seize Lubricant

Product type: Lubricant

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 235092 Item number: 80209 Region: United States

Contact information: Telephone: 860.571.5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

Physical state:pasteHEALTH:\*1Color:silverFLAMMABILITY:1Odor:Hydrocarbon-likePHYSICAL HAZARD:0

Personal Protection: See MSDS Section 8

WARNING: CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

**Potential Health Effects** 

**Inhalation:** Moderate respiratory tract irritation.

Skin contact: Moderate skin irritation.

Eye contact: Moderate eye irritation.

**Ingestion:** Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis. Ingestion

may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	10 - 30
Graphite	7782-42-5	10 - 30
Calcium oxide	1305-78-8	10 - 30
Mineral oil light naphthenic hydrotreat. <3% DMSO	64742-53-6	10 - 30
Aluminum not powder, dust or fume	7429-90-5	5 - 10
Distillates (petroleum), straight-run middle	64741-44-2	1 - 5
Quartz (SiO2)	14808-60-7	0.1 - 1

## 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: If symptoms develop and persist, get medical attention. Wash with soap and

water.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

**Ingestion:** Do not induce vomiting. Get immediate medical attention.

## 5. FIRE FIGHTING MEASURES

Flash point:  $> 93 \, ^{\circ}\text{C} \, (> 199.4 \, ^{\circ}\text{F})$ 

Autoignition temperature: Not determined

Flammable/Explosive limits - lower: Not available.

Flammable/Explosive limits - upper: Not available.

Extinguishing media: Dry chemical. Carbon dioxide. foam

Special firefighting procedures: None

Unusual fire or explosion hazards: None

IDH number: 235092

**Hazardous combustion products:** Oxides of carbon. Oxides of nitrogen.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so.

Clean-up methods: Store in a partly filled, closed container until disposal. Soak up with inert

absorbent material (e.g. sand, silica gel, acid binder, universal binder,

sawdust). Remove all sources of ignition.

## 7. HANDLING AND STORAGE

Handling: Keep away from heat, spark and flame. Avoid skin and eye contact.

Storage: Keep in a cool, well ventilated area.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist 500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Graphite	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 MPPCF TWA	None	None
Calcium oxide	2 mg/m3 TWA	5 mg/m3 PEL	None	None
Mineral oil light naphthenic hydrotreat. <3% DMSO	None	500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Aluminum not powder, dust or fume	1 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL (as Al) Respirable dust. 15 mg/m3 PEL (as Al) Total dust.	None	None
Distillates (petroleum), straight-run middle	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: An approved mask or respirator fitted with an organic vapour cartridge should

be worn if the product is used in a poorly ventilated area

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Neoprene or oil resistant gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: paste
Color: silver

Odor: Hydrocarbon-like
Odor threshold: Not available.
pH: Not applicable
Vapor pressure: <5 mm hg
Boiling point/range: Not available.
Melting point/ range: Not available.
Specific gravity: 1.25

Vapor density:

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Not available.

Not determined

Not available.

Insoluble

VOC content: < 3 %

Partition coefficient (n-octanol/water):

Not available.

# 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

**Hazardous decomposition** 

products:

None reasonably foreseeable.

Incompatible materials: Strong oxidizing agents.

Conditions to avoid: None known

## 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Graphite	No	No	No
Calcium oxide	No	No	No
Mineral oil light naphthenic hydrotreat. <3% DMSO	No	No	No
Aluminum not powder, dust or fume	No	No	No
Distillates (petroleum), straight-run middle	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	No

Hazardous components	Health Effects/Target Organs		
Distillates (petroleum), hydrotreated heavy naphthenic	Irritant		
Graphite	Lung		
Calcium oxide	Irritant, Corrosive, Eyes		
Mineral oil light naphthenic hydrotreat. <3% DMSO	Irritant		
Aluminum not powder, dust or fume	Central nervous system, Irritant, Lung		
Distillates (petroleum), straight-run middle	Irritant		
Quartz (SiO2)	Immune system, Lung, Some evidence of carcinogenicity		

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:**Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

IDH number: 235092 Product name: Silver Grade Anti-Seize Lubricant

#### International Air Transportation (ICAO/IATA)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

# 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Aluminum not powder, dust or fume (CAS# 7429-90-5).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

#### **Canada Regulatory Information**

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.A, D.2.B

#### 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Updated Contact Information in Section 1., Updated HMIS rating in Section 2.

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.