



SAFETY DATA SHEET

1. Identification

| | |
|---|---|
| Product identifier | Marine Heavy Duty Silicone™ |
| Other means of identification | |
| Product code | 06077 |
| Recommended use | Silicone-based multi-purpose lubricant |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Manufactured or sold by: | |
| Company name | CRC Industries, Inc. |
| Address | 885 Louis Dr. Warminster, PA 18974 US |
| Telephone | |
| General Information | 215-674-4300 |
| Technical Assistance | 800-521-3168 |
| Customer Service | 800-272-4620 |
| 24-Hour Emergency (CHEMTREC) | 800-424-9300 (US) 703-527-3887 (International) |
| Website | www.crcindustries.com |

2. Hazard(s) identification

| | | |
|------------------------------|--|---|
| Physical hazards | Flammable aerosols Gases under pressure | Category 1 Liquefied gas |
| Health hazards | Skin corrosion/irritation Serious eye damage/eye irritation Specific target organ toxicity, single exposure Aspiration hazard | Category 2 Category 2 Category 3 narcotic effects Category 1 |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard Hazardous to the aquatic environment, long-term hazard | Category 1 Category 1 |
| OSHA defined hazards | Not classified. | |

Label elements



| | |
|--------------------------------|---|
| Signal word | Danger |
| Hazard statement | Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. |
| Precautionary statement | |
| Prevention | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear protective gloves and eye/face protection. Avoid release to the environment. |

| | |
|--|--|
| Response | If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Collect spillage. |
| Storage | Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. |
| Disposal | Dispose of contents/container in accordance with local/regional/national regulations. |
| Hazard(s) not otherwise classified (HNOC) | Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion. |
| Supplemental information | 35.39% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 35.39% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|------------|---------|
| Acetone | | 67-64-1 | 30 - 40 |
| Liquefied Petroleum Gas | | 68476-86-8 | 20 - 30 |
| 3-Methylhexane | | 589-34-4 | 5 - 10 |
| Naphtha (petroleum), hydrotreated light | | 64742-49-0 | 5 - 10 |
| n-Heptane | | 142-82-5 | 5 - 10 |
| Methylcyclohexane | | 108-87-2 | 3 - 5 |
| Polydimethylsiloxane | | 63148-62-9 | 3 - 5 |
| Cyclohexane | | 110-82-7 | 1 - 3 |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|--|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
| Skin contact | Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|---|---|
| Suitable extinguishing media | Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed. |

| | |
|--|---|
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire-fighting equipment/instructions | In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. |
| General fire hazards | Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Remove all possible sources of ignition in the surrounding area. Many vapors are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination. |

7. Handling and storage

| | |
|---|---|
| Precautions for safe handling | Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. For product usage instructions, please see the product label. |
| Conditions for safe storage, including any incompatibilities | Level 3 Aerosol. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|----------------------------------|------|------------------------|
| Acetone (CAS 67-64-1) | PEL | 2400 mg/m3 1000 ppm |
| Cyclohexane (CAS 110-82-7) | PEL | 1050 mg/m3 300 ppm |
| Methylcyclohexane (CAS 108-87-2) | PEL | 2000 mg/m3 500 ppm |
| n-Heptane (CAS 142-82-5) | PEL | 2000 mg/m3 500 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|----------------------------------|------|---------|
| 3-Methylhexane (CAS 589-34-4) | STEL | 500 ppm |
| | TWA | 400 ppm |
| Acetone (CAS 67-64-1) | STEL | 750 ppm |
| | TWA | 500 ppm |
| Cyclohexane (CAS 110-82-7) | TWA | 100 ppm |
| | STEL | 500 ppm |
| Methylcyclohexane (CAS 108-87-2) | TWA | 400 ppm |
| | STEL | 500 ppm |
| n-Heptane (CAS 142-82-5) | STEL | 500 ppm |
| | TWA | 400 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|----------------------------------|---------|------------|
| Acetone (CAS 67-64-1) | TWA | 590 mg/m3 |
| | | 250 ppm |
| Cyclohexane (CAS 110-82-7) | TWA | 1050 mg/m3 |
| | | 300 ppm |
| Methylcyclohexane (CAS 108-87-2) | TWA | 1600 mg/m3 |
| | | 400 ppm |
| n-Heptane (CAS 142-82-5) | Ceiling | 1800 mg/m3 |
| | | 440 ppm |
| | TWA | 350 mg/m3 |
| | | 85 ppm |

Biological limit values**ACGIH Biological Exposure Indices**

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------|---------|-------------|----------|---------------|
| Acetone (CAS 67-64-1) | 50 mg/l | Acetone | Urine | * |

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection**Hand protection**

Wear protective gloves such as: Nitrile. Polyvinyl alcohol (PVA). Viton®.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance****Physical state**

Liquid.

Form

Aerosol.

Color

Water-white.

Odor

Solvent.

| | |
|---|------------------------------------|
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | -195.9 °F (-126.6 °C) estimated |
| Initial boiling point and boiling range | 132.9 °F (56.1 °C) estimated |
| Flash point | < 0 °F (< -17.8 °C) Tag Closed Cup |
| Evaporation rate | Fast. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | 1.1 % estimated |
| Flammability limit - upper (%) | 12.8 % estimated |
| Vapor pressure | 1518.9 hPa estimated |
| Vapor density | > 1 (air = 1) |
| Relative density | 0.69 estimated |
| Solubility (water) | Slightly soluble. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 539.6 °F (282 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity (kinematic) | Not available. |
| Percent volatile | 97 % estimated |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Acids. Aldehydes. Alkalies. Amines. Ammonia. Halogens. Peroxides. Reducing agents. Strong acids. Strong bases. Strong oxidizing agents. |
| Hazardous decomposition products | Carbon oxides. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | May cause drowsiness and dizziness. Headache. Nausea, vomiting. |
| Skin contact | Causes skin irritation. |
| Eye contact | Causes serious eye irritation. |
| Ingestion | Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. |

Symptoms related to the physical, chemical and toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

| Product | Species | Test Results |
|---------|---------|--------------|
|---------|---------|--------------|

Marine Heavy Duty Silicone™

Acute

Dermal

LD50

Rabbit

5404 mg/kg estimated

| Product | Species | Test Results |
|-------------------|---------|-----------------------------|
| Inhalation | | |
| LC50 | Rat | 100 mg/l, 4 Hours estimated |
| Oral | | |
| LD50 | Rat | 7617 mg/kg estimated |

* Estimates for product may be based on additional component data not shown.

| | |
|---|---|
| Skin corrosion/irritation | Causes skin irritation. |
| Serious eye damage/eye irritation | Causes serious eye irritation. |
| Respiratory sensitization | Not a respiratory sensitizer. |
| Skin sensitization | This product is not expected to cause skin sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. |
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. |
| Specific target organ toxicity - single exposure | May cause drowsiness and dizziness. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. |

12. Ecological information

| Product | Species | Test Results | |
|---------------------------------------|---|--|-------------------------------------|
| Ecotoxicity | Very toxic to aquatic life with long lasting effects. | | |
| Marine Heavy Duty Silicone™ | | | |
| Aquatic | | | |
| Crustacea | EC50 | Daphnia | 79213.0703 mg/l, 48 hours estimated |
| <i>Acute</i> | | | |
| Fish | LC50 | Fish | 22.6832 mg/l, 96 hours estimated |
| Components | Species | Test Results | |
| Acetone (CAS 67-64-1) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 10294 - 17704 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout, donaldson trout (Oncorhynchus mykiss) | 4740 - 6330 mg/l, 96 hours |
| Cyclohexane (CAS 110-82-7) | | | |
| Aquatic | | | |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | 23.03 - 42.07 mg/l, 96 hours |
| Methylcyclohexane (CAS 108-87-2) | | | |
| Aquatic | | | |
| Fish | LC50 | Striped bass (Morone saxatilis) | 5.8 mg/l, 96 hours |
| n-Heptane (CAS 142-82-5) | | | |
| Aquatic | | | |
| <i>Acute</i> | | | |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | 2.1 - 2.98 mg/l, 96 hours |
| Polydimethylsiloxane (CAS 63148-62-9) | | | |
| Aquatic | | | |
| Fish | LC50 | Channel catfish (Ictalurus punctatus) | 2.36 - 4.15 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|-------------------|-------|
| Acetone | -0.24 |
| Cyclohexane | 3.44 |
| Methylcyclohexane | 3.61 |
| n-Heptane | 4.66 |

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, flammable, Limited Quantity, MARINE POLLUTANT (Heptanes) |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Label(s) | 2.1 |
| Packing group | Not applicable. |
| Environmental hazards | |
| Marine pollutant | Yes |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions | N82 |
| Packaging exceptions | 306 |
| Packaging non bulk | None |
| Packaging bulk | None |

IATA

| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, flammable, Limited Quantity |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Packing group | Not applicable. |
| Environmental hazards | Yes. |
| ERG Code | 10L |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Allowed. |
| Cargo aircraft only | Allowed. |

IMDG

| | |
|-------------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | AEROSOLS, LIMITED QUANTITY, MARINE POLLUTANT |
| Transport hazard class(es) | |
| Class | 2 |
| Subsidiary risk | - |
| Packing group | Not applicable. |
| Environmental hazards | |
| Marine pollutant | Yes |
| EmS | Not available. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Cyclohexane (CAS 110-82-7)

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.

Cyclohexane (CAS 110-82-7) Listed.

CERCLA Hazardous Substances: Reportable quantity

Acetone (CAS 67-64-1) 5000 LBS

Cyclohexane (CAS 110-82-7) 1000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes

Hazard categories Delayed Hazard - No

Fire Hazard - Yes

Pressure Hazard - Yes

Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

Liquefied Petroleum Gas (CAS 68476-86-8)

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

3-Methylhexane (CAS 589-34-4)

Acetone (CAS 67-64-1)

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5)

Cyclohexane (CAS 110-82-7)

US. Massachusetts RTK - Substance List

3-Methylhexane (CAS 589-34-4)

Acetone (CAS 67-64-1)
Cyclohexane (CAS 110-82-7)
Methylcyclohexane (CAS 108-87-2)
n-Heptane (CAS 142-82-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)
Cyclohexane (CAS 110-82-7)
Toluene (CAS 108-88-3)
3-Methylhexane (CAS 589-34-4)
Methylcyclohexane (CAS 108-87-2)
n-Heptane (CAS 142-82-5)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
Cyclohexane (CAS 110-82-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

| | |
|-----------------------------|---------------------------|
| Benzene (CAS 71-43-2) | Listed: February 27, 1987 |
| Cumene (CAS 98-82-8) | Listed: April 6, 2010 |
| Ethanal (CAS 75-07-0) | Listed: April 1, 1988 |
| Ethylbenzene (CAS 100-41-4) | Listed: June 11, 2004 |
| Naphthalene (CAS 91-20-3) | Listed: April 19, 2002 |

US - California Proposition 65 - CRT: Listed date/Developmental toxin

| | |
|------------------------|---------------------------|
| Benzene (CAS 71-43-2) | Listed: December 26, 1997 |
| Toluene (CAS 108-88-3) | Listed: January 1, 1991 |

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

| | |
|------------------------|------------------------|
| Toluene (CAS 108-88-3) | Listed: August 7, 2009 |
|------------------------|------------------------|

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

| | |
|-----------------------|---------------------------|
| Benzene (CAS 71-43-2) | Listed: December 26, 1997 |
|-----------------------|---------------------------|

Volatile organic compounds (VOC) regulations

EPA

| | |
|--|---------------|
| VOC content (40 CFR 51.100(s)) | 59.5 % |
| Consumer products (40 CFR 59, Subpt. C) | Not regulated |

State

| | |
|--------------------------|--|
| Consumer products | This product is regulated as a Silicone Based Multi-Purpose Lubricant. This product is compliant for use in all 50 states. |
| VOC content (CA) | 59.5 % |
| VOC content (OTC) | 59.5 % |

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|-------------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | Yes |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|----------------------------|--|
| Issue date | 05-07-2015 |
| Prepared by | Allison Cho |
| Version # | 01 |
| Further information | Not available. |
| HMIS® ratings | Health: 2 Flammability: 4 Physical hazard: 0 Personal protection: B |
| NFPA ratings | Health: 2 Flammability: 4 Instability: 0 |

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.