# **MATERIAL SAFETY DATA SHEET**

**S00728000 DATE OF PREPARATION 02 00**May 7, 2014

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

## **PRODUCT NUMBER**

S00728000

#### PRODUCT NAME

LU™728 Non-Flammable Synthetic Lubricant Aerosol

#### **MANUFACTURER'S NAME**

Sprayon Products Cleveland, OH 44115

**Telephone Numbers and Websites** 

relepitotie ivuitibers allu vvebsiles			
Product Information	(800) 247-3266		
	www.sprayon.com		
Regulatory Information	(216) 566-2902		
Medical Emergency	gency (216) 566-2917		
Transportation Emergency*	(800) 424-9300		
*for Chemical Emergency ONLY (spill, leak, fire, exposure, or			
	accident)		

# SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
95	Proprietary	Polyolefin		
		ACGIH TLV	Not Available	
		OSHA PEL	Not Available	
2	124-38-9	Carbon Dioxide		
		ACGIH TLV	5000 PPM	760 mm
		OSHA PEL	5000 PPM	

## **SECTION 3 — HAZARDS IDENTIFICATION**

### **ROUTES OF EXPOSURE**

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

#### **EFFECTS OF OVEREXPOSURE**

EYES: Irritation.

**SKIN:** Prolonged or repeated exposure may cause irritation.

**INHALATION:** Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

## SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

# MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

#### **CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

# **SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.

**SKIN:** Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

# **SECTION 5 — FIRE FIGHTING MEASURES**

HMIS Codes Health 1

Flammability 0 Reactivity 0 **FLASH POINT** LEL UEL **EXTINGUISHING MEDIA** > 200 °F PMCC Not Not Carbon Dioxide, Dry Chemical, Foam

Applicable **UNUSUAL FIRE AND EXPLOSION HAZARDS** Applicable

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

## SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

# **SECTION 6 — ACCIDENTAL RELEASE MEASURES**

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

## SECTION 7 — HANDLING AND STORAGE

#### STORAGE CATEGORY

Not Applicable

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

## SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION

#### PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

#### VENTII ATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

# RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

# **PROTECTIVE GLOVES**

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

## **EYE PROTECTION**

Wear safety spectacles with unperforated sideshields.

## SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT 6.80 lb/gal 814 g/l

SPECIFIC GRAVITY 0.82

<-18 - -77 °C **BOILING POINT** <0 - -108 °F

**MELTING POINT** Not Available **VOLATILE VOLUME** 1%

**EVAPORATION RATE** Faster than

ether

VAPOR DENSITY Heavier than air SOLUBILITY IN WATER Not Available

VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)

Volatile Weight 0.00% Less Water and Federally Exempt Solvents

## SECTION 10 — STABILITY AND REACTIVITY

STABILITY — Stable **CONDITIONS TO AVOID** 

None known.

**INCOMPATIBILITY** 

None known.

#### **HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

#### **HAZARDOUS POLYMERIZATION**

Will not occur

## **SECTION 11 — TOXICOLOGICAL INFORMATION**

#### **CHRONIC HEALTH HAZARDS**

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

#### **TOXICOLOGY DATA**

CAS No.	Ingredient Name				
Proprietary	Polyolefin				
	•	LC50 RAT	4HR	Not Available	
		LD50 RAT		Not Available	
124-38-9	Carbon Dioxide				
		LC50 RAT	4HR	Not Available	
		LD50 RAT		Not Available	

# **SECTION 12 — ECOLOGICAL INFORMATION**

#### **ECOTOXICOLOGICAL INFORMATION**

No data available.

## **SECTION 13 — DISPOSAL CONSIDERATIONS**

#### WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

### SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

#### **US Ground (DOT)**

May be classed as LTD. QTY. OR ORM-D

UN1950, AEROSOLS, 2.2, LIMITED QUANTITY, (ERG#126)

### Canada (TDG)

May be classed as LTD. QTY. OR ORM-D

UN1950, AEROSOLS, CLASS 2.2, LIMITED QUANTITY, (ERG#126)

#### IMO

May be shipped as Limited Quantity

UN1950, AEROSOLS, CLASS 2.2, LIMITED QUANTITY, EmS F-D, S-U

### IATA/ICAO

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, LIMITED QUANTITY

# **SECTION 15 — REGULATORY INFORMATION**

## SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
OAO NO.		1 /0 DY VV I	/0 LICITICITE

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

## **TSCA CERTIFICATION**

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

# **SECTION 16 — OTHER INFORMATION**

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.