# **Material Safety Data Sheet**





Revision Number: 006.0 Issue date: 09/27/2012

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE® 565™ PST® PIPE SEALANT IDH number: 88551

h PTFE THREAD SEALANT

Product type: Anaerobic Sealant Item number: 56531
Region: United States

Company address: Contact information:

Henkel Electronic Materials LLC

14000 Jamboree Road

Irvine, CA 92606

Telephone: 1.888.9.HENKEL (1.888.943.6535)

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

Physical state: Paste HEALTH: \*2
Color: White FLAMMABILITY: 1

Odor: Mild PHYSICAL HAZARD: 1
Personal Protection: See MSDS Section 8

WARNING: CAUSES EYE IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

**Potential Health Effects** 

**Inhalation:** May cause respiratory tract irritation.

**Skin contact:** May cause allergic skin reaction. May cause skin irritation.

**Eye contact:** Contact with eyes will cause irritation. **Ingestion:** Not expected to be harmful by ingestion.

Existing conditions aggravated by

exposure:

IDH number: 88551

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

Product name: LOCTITE® 565™ PST® PIPE SEALANT h PTFE THREAD SEALANT

Page 1 of 6

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Polyglycol dimethacrylate	25852-47-5	30 - 60
Hexanedioic acid, polymer with 1,4-butanediol and 1,2- propanediol, dodecanoate	68186-73-2	10 - 30
Cellulose ester	9004-36-8	10 - 30
Ethene, tetrafluoro-, homopolymer	9002-84-0	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Treated fumed silica	67762-90-7	1 - 5
Saccharin	81-07-2	1 - 5
Cumene hydroperoxide	80-15-9	1 - 5
Ethylene glycol	107-21-1	0.1 - 1
Cumene	98-82-8	0.1 - 1

## 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Wash clothing before reuse.

Wash with soap and water. If symptoms develop and persist, get medical

attention.

**Eye contact:** Get medical attention. Flush with copious amounts of water, preferably,

lukewarm water for at least 15 minutes, holding eyelids open all the time.

Ingestion: Keep individual calm. Do not induce vomiting. Get medical attention.

## 5. FIRE FIGHTING MEASURES

Flash point: > 93.3 °C (> 199.94 °F)

Autoignition temperature: Not available.

Flammable/Explosive limits - upper: Not available.

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Not available.

Unusual fire or explosion hazards: None

Flammable/Explosive limits - lower:

Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Toxic fluorine

compounds. Irritating organic vapours.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Store in a partly filled, closed container until

disposal.

IDH number: 88551 Product name: LOCTITE® 565™ PST® PIPE SEALANT h PTFE THREAD SEALANT

Page 2 of 6

# 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing.

For safe storage, store at or below 38 °C (100.4 °F) Storage:

Keep in a cool, well ventilated area.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Hexanedioic acid, polymer with 1,4-butanediol and 1,2-propanediol, dodecanoate	None	None	None	None
Cellulose ester	None	None	None	None
Ethene, tetrafluoro-, homopolymer	None	None	None	10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 TWA Total dust.	None	None
Treated fumed silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Saccharin	None	None	None	None
Cumene hydroperoxide	None	None	(SKIN) 1 ppm (6 mg/m3) TWA	None
Ethylene glycol	100 mg/m3 Ceiling Aerosol.	None	None	None
Cumene	50 ppm TWA	50 ppm (245 mg/m3) TWA (SKIN)	None	None

**Engineering controls:** No specific ventilation requirements noted, but forced ventilation may still be

required if concentrations exceed occupational exposure limits.

Respiratory protection: Use a NIOSH approved supplied air respirator with an organic cartridge if the

potential to exceed established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Neoprene, Butyl-rubber, or nitrile-rubber gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste Color: White Mild Odor: Not available. Odor threshold: pH: Not applicable

< 5 mm hg (27 °C (80.6 °F)) Vapor pressure: > 149 °C (> 300.2 °F) Boiling point/range:

Melting point/ range: Not available.

Specific gravity: 1.1

Vapor density: Not available.

Flash point: > 93.3 °C (> 199.94 °F)

Flammable/Explosive limits - lower: Not available.

Product name: LOCTITE® 565™ PST® PIPE SEALANT IDH number: 88551 h PTFE THREAD SEALANT

Page 3 of 6

Flammable/Explosive limits - upper:
Autoignition temperature:
Not available.
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
VOC content:
Not available.
Not available.
0.11 %; 1.06 g/l

## 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of carbon. Toxic fluorine compounds. Oxides of nitrogen. Oxides of

sulfur. Irritating organic vapours.

**Incompatible materials:** Strong oxidizing agents.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

## 11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 5,000 mg/kg (Estimated)

Acute dermal product toxicity: LD50 (rabbit) > 2,000 mg/kg (Estimated)

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dimethacrylate	No	No	No
Hexanedioic acid, polymer with 1,4- butanediol and 1,2-propanediol, dodecanoate	No	No	No
Cellulose ester	No	No	No
Ethene, tetrafluoro-, homopolymer	No	No	No
Titanium dioxide	No	Group 2B	No
Treated fumed silica	No	No	No
Saccharin	No	No	No
Cumene hydroperoxide	No	No	No
Ethylene glycol	No	No	No
Cumene	No	Group 2B	No

Hazardous components	Health Effects/Target Organs
Polyglycol dimethacrylate	Irritant, Allergen
Hexanedioic acid, polymer with 1,4-butanediol and 1,2-propanediol, dodecanoate	No Records
Cellulose ester	No Target Organs
Ethene, tetrafluoro-, homopolymer	No Target Organs
Titanium dioxide	Irritant, Respiratory, Some evidence of carcinogenicity
Treated fumed silica	Irritant
Saccharin	No Target Organs
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
Ethylene glycol	Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic
Cumene	Central nervous system, Irritant, Lung

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 88551 Product name: LOCTITE® 565™ PST® PIPE SEALANT h PTFE THREAD SEALANT

Page 4 of 6

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:**Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

#### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## 15. REGULATORY INFORMATION

### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Cumene hydroperoxide (CAS# 80-15-9).

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm. This product contains a chemical known in the State of California

to cause cancer.

#### **Canada Regulatory Information**

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.A, D.2.B

## 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 1, 3, 8, 11, 15

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

IDH number: 88551 Product name: LOCTITE® 565™ PST® PIPE SEALANT h PTFE THREAD SEALANT

Page 5 of 6

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: LOCTITE® 565™ PST® PIPE SEALANT h PTFE THREAD SEALANT

Page 6 of 6

IDH number: 88551