

ISO-9001 Registered Quality System. ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE No. 35 SOLUBLE OIL

WATER SOLUBLE CUTTING AND GRINDING FLUID

LUBRIPLATE No. 35 SOLUBLE OIL is a soluble oil concentrate. This product was designed to be extended with water for the machining and grinding of virtually all metals except magnesium.

<u>ADVANTAGES</u>

- · Operator Friendly
- Low Foaming
- Mild, Pleasant Odor
- Excellent Corrosion Inhibition

- · Sulfur and Chlorine Free
- Excellent Hard Water Stability
- Clean Running
- Provides Excellent Finish

APPLICATIONS

Designed for use in metalworking applications such as all CNC milling, turning, drilling, tapping and grinding. **LUBRIPLATE No. 35 SOLUBLE OIL** is also suitable for light-duty stamping operations. Suggested mixture: 1:3 to 1:10 based upon results obtained from the mixture.

RECOMMENDED STARTING DILUTIONS

Centerless, ID, OD, Surface Grinding
Milling, Drilling, Turning
Tapping, Reaming, Sawing
25:1 (4%)
20:1 (5%)
10:1 (10%)

(Over)

LUBRIPLATE No. 35 SOLUBLE OIL

TYPICAL PROPERTIES

Brown Clear Liquid Appearance - concentrate Appearance - dilution Opaque White Bland Odor Residual Film Soft, Fluid Specific Gravity @ 60°F 0.919 ± 0.01 **API** Gravity 22.5 Lbs/Gallon 7.65 ± 0.1 Flash Point - COC 355°F/179°C

LUBRIPLATE No. 35 SOLUBLE OIL

CONCENTRATION

CONCENTRATION	4%	5%	6%	7%	8%	9%	10%
	(1:25)	(1:20)	(1:17)	(1:14)	(1:12)	(1:11)	(1:10)
REFRACTOMETER READING	4.4	5.4	7.0	8.0	9.0	10.2	11.4

(An optical refractometer may be used for determining concentration)

<u>Packaging Available</u>	<u>Part Number</u>
Ctn. 4/1 Gallon Jugs	L0576-057
5 Gallon Pail	L0576-060
16 Gallon Drum	L0576-061
55 Gallon Drum	L0576-062

All reasonable care has been taken to ensure that the above information is accurate as of the date of printing.

Material Safety Data Sheet available upon request.