Section 1: Product & Company Identification

Product Name: Air Tool Oil

Product Number (s): SL2531, SL2533, 74095

Product Use: lubricant for pneumatic equipment

Manufacturer / Supplier Contact Information:

<u>In United States</u>: <u>In Canada</u>: <u>In Mexico</u>:

CRC Industries, Inc.

CRC Canada Co.

CRC Industries Mexico

2-1246 Lorimar Drive

Av. Benito Juárez 4055 G

Warminster, PA 18974 Mississauga, Ontario L5S 1R2 Colonia Orquídea

<u>www.crcindustries.com</u> <u>www.crc-canada.ca</u> San Luís Potosí, SLP CP 78394 1-215-674-4300(General) 1-905-670-2291 <u>www.crc-mexico.com</u>

1-215-674-4300 (General) (800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

24-Hr Emergency - CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

52-444-824-1666

As defined by OSHA's Hazard Communication Standard, this product is non-hazardous.

Appearance & Odor: Amber viscous liquid, faint petroleum odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: Direct contact irritates slightly with redness and swelling.

SKIN: Slightly irritating. Repeated or prolonged contact can result in drying of the skin.

INHALATION: Inhalation hazard at room temperature is unlikely due to the low volatility of this product. Heating

can generate vapors that may cause respiratory irritation, nausea and headaches.

INGESTION: May cause stomach pain or vomiting. Main hazard, if ingested, is aspiration into the lungs and

subsequent pneumonitis.

CHRONIC EFFECTS: Unknown
TARGET ORGANS: Unknown

Medical Conditions Aggravated by Exposure: Unknown

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Number (s): SL2531, SL2533, 74095

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.	
Hydrotreated light naphthenic distillates	64742-53-6	93 – 97	
Solvent-refined heavy naphthenic distillates	64741-96-4	1 – 5	
Zinc, dithiophosphate di-C1-14-alkyl esters	68649-42-3	< 1	

Section 4: First Aid Measures

Product Name: Air Tool Oil

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if

irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: Do NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an

unconscious person.

Note to Physicians: If product is injected into or under the skin, or into any part of the body, the individual should be

evaluated immediately as a surgical emergency. Even though symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may

significantly reduce the ultimate extent of injury.

Section 5: Fire-Fighting Measures

Flammable Properties: As defined by OSHA, this product is a nonflammable.

Flash Point: > 300°F (COC) Upper Explosive Limit: ND

Autoignition Temperature: ND Lower Explosive Limit: ND

Fire and Explosion Data:

Suitable Extinguishing Media: Foam, dry chemicals, sand, dolomite, carbon dioxide

Products of Combustion: Acrid smoke/fumes; oxides of carbon

Explosion Hazards: Containers, when exposed to heat from fire, may build pressure and rupture.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool

and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8. Minimize skin contact

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into

sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space

or limited air circulation area, clean-up workers should wear appropriate

respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Do not reuse container. Keep container closed when not in use. Ventilate well and avoid

breathing vapors. Do not store or mix with strong oxidizers. Avoid strong heating. For product

use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Containers should be tightly closed while in

storage. Keep away from sources of ignition. Store away from strong acids and oxidizers.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	OSHA		ACGIH		OTHER		
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
II. day to a start Park a said than Said Partition	_	NIT.	0.0	NE	NIE		3
Hydrotreated light naphthenic distillates	5	NE	0.2	NE	NE		mg/m ³
Solvent-refined heavy naphthenic distillates	5	NE	0.2	NE	NE		mg/m ³
Zinc, dithiophosphate di-C1-14-alkyl esters	NE	NE	NE	NE	NE		
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally

preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA

regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls

are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and

for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or PVC. Also, use full protective clothing if there is

prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid (viscous)

Color: amber

Odor: mild petroleum Odor Threshold: ND Specific Gravity: 0.91 Product Name: Air Tool Oil Product Number (s): SL2531, SL2533, 74095

Initial Boiling Point: > 360°F Freezing Point: ND Vapor Pressure: ND

Vapor Density: > 1 (air = 1)

Evaporation Rate: slow Solubility: insoluble in water

Coefficient of water/oil distribution: ND

pH: NA

Volatile Organic Compounds: wt %: 0 g/L: 0 lbs./gal: 0

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition

Incompatible Materials: Strong acids and oxidizers

Hazardous Decomposition Products: Oxides of carbon, sulfur and phosphorus

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

Component Hydrotreated light naphthenic distillates	<u>Oral LD50</u> (rat) > 5000 mg/kg	Dermal LD50 (rabbit) > 2000 mg/kg	Inhalation LC50 (rat) 2.18 mg/L/4H
Solvent-refined heavy naphthenic distillates	No data	No data	No data
Zinc, dithiophosphate di-C1-14-alkyl esters	No data	No data	No data

Chronic Toxicity:

	OSHA	IARC	NTP		
<u>Component</u>	Carcinogen	Carcinogen	<u>Carcinogen</u>	<u>Irritant</u>	<u>Sensitizer</u>
Hydrotreated light naphthenic	No	No	No	E (mild) /	Unknown
distillates				S (mild)	
Solvent-refined heavy naphthenic	No	No	No	Unknown	Unknown
distillates					
Zinc, dithiophosphate di-C1-14-alkyl	No	No	No	Unknown	Unknown
esters					

E – Eye S – Skin R - Respiratory

Reproductive Toxicity:
Teratogenicity:
Mutagenicity:
Synergistic Effects:
No information available
No information available
No information available

Other: IARC has determined in reviewing cancer prevalence of exposed workers that

the carcinogenic activity of refined oils is related to the severity of processing of the base oil. The base oils in this product contain < 3% DMSO Extractable total

polycyclic aromatic compound (PAC) per IP 346.

Product Number (s): SL2531, SL2533, 74095

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: No information available

Product Name: Air Tool Oil

Persistence / Degradability:
Bioaccumulation / Accumulation:
Mobility in Environment:

No information available
No information available

Section 13: Disposal Considerations

<u>Waste Classification</u>: This product is not a RCRA hazardous waste as packaged. (See 40 CFR Part 261.20 – 261.33)

Used oil should be collected and handled in accordance with 40 CFR Part 279. Used oil that is

mixed with hazardous waste may be subject to regulation as hazardous waste. Empty

containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): Not Regulated

ICAO/IATA (air): Not Regulated

IMO/IMDG (water): Not Regulated

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard No

Reactive Hazard No Release of Pressure No Acute Health Hazard No Chronic Health Hazard No

Product Number (s): SL2531, SL2533, 74095

Section 313 Toxic Chemicals:

Product Name: Air Tool Oil

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of

1986 and 40 CFR Part 372:

Zinc, dithiophosphate di-C1-14-alkyl esters (zinc compounds): < 1%

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

N-Methylpyrrolidone (< 35 ppm)

Consumer Products VOC Regulations: This product is not regulated.

State Right to Know:

New Jersey: Petroleum Oil Pennsylvania: None Massachusetts: 64742-53-6 Rhode Island: None

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: Not Regulated

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.

European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the

Council of 27 January 2003. This product does not contain any of the restricted substances as

listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information


HMIS® (II)		
Health:	1	
Flammability:	1	
Reactivity:	0	
PPE:	В	

Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick CRC #: 720090

Revision Date: 08/02/2012

Changes since last revision: **Revision Date**



Product Name: Air Tool Oil

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists NA: CAS: Chemical Abstract Service ND:

CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substance List

g/L: grams per Liter

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer

IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 IMDG: International Maritime Dangerous Goods
 IMO: International Maritime Organization

IMO: International Maritime lbs./gal: pounds per gallon LC: Lethal Concentration

LD: Lethal Dose

NA: Not Applicable ND: Not Determined

NIOSH: National Institute of Occupational Safety & Health

NFPA: National Fire Protection Association

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PMCC: Pensky-Martens Closed Cup
PPE: Personal Protection Equipment

ppm: Parts per Million

RoHS: Restriction of Hazardous Substances

STEL: Short Term Exposure Limit

TCC: Tag Closed Cup
TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Information

System