



Revision Date: 01/25/2006

Issue date: 02/08/2006

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Thread Sealant with PTFE
Product type: Sealant
Company address: Henkel Corporation
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067

Item No.: 30534
Region: United States
Contact Information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Isopropyl alcohol 67-63-0	30-60	200 ppm TWA 400 ppm STEL	400 ppm TWA 980 mg/m ³ TWA	None
Talc 14807-96-6	10-30	2 mg/m ³ TWA respirable fraction, particulate matter containing no asbestos and < 1% crystalline silica	= 20 mppcf TWA	50 ppm
Castor Oil	10-30	None	None	None
Vinyl terpolymer 27360-07-2	10-30	None	None	None
Titanium dioxide 13463-67-7	1-5	10 mg/m ³ TWA	15 mg/m ³ TWA total dust	None
Poly(tetrafluoroethylene) 9002-84-0	1-5	None	None	AEL (DuPont): 10 mg/m ³ , 8 Hr TWA, total dust; 5mg/m ³ , 8 hr. TWA respirable dust
Silica, quartz 14808-60-7	0.1-1	0.05 mg/m ³ TWA respirable fraction	0.1mg/m ³ TWA (respirable)	None

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state: Paste	HEALTH:	2*
Color: White	FLAMMABILITY:	3
Odor: Alcoholic	PHYSICAL HAZARD:	0
	Personal Protection:	See Section 8

WARNING: FLAMMABLE LIQUID AND VAPOR.
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Inhalation, Ingestion, Eye contact, Skin contact

Potential Health Effects

Inhalation: Vapors may cause headaches, nausea, dizziness and respiratory tract irritation.
Skin contact: Irritating to skin.
Eye contact: Vapors may irritate eyes. Contact with eyes will cause irritation.
Ingestion: Contains material that may be slightly toxic.

Item No. : 30534

Product name: Thread Sealant with PTFE

Existing conditions aggravated by exposure:

Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If discomfort persists seek medical attention.

Skin contact: Wash with soap and water.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash point: 23.3°C (74°F) Tagliabue closed cup

Autoignition temperature: 398.3°C (750°F) estimated

Flammable/Explosive limits-lower %: 2.3 %

Flammable/Explosive limits-upper %: 12.7 %

Extinguishing media: Use dry chemical, CO2, water spray or `alcohol` foam.

Special fire fighting procedures: N/A

Unusual fire or explosion hazards: None

Hazardous combustion products: Toxic fluorides.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Remove sources of ignition. Ventilate area.

Clean-up methods: Remove all sources of ignition. Ventilate area. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Contain the spill in a closed container until disposal.

7. HANDLING AND STORAGE

Handling: Keep away from heat, spark and flame. Do not get in eyes.

Storage: Store away from heat, sparks, flames, or other sources of ignition.

Incompatible products: Oxidizing agents.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Use local exhaust ventilation to maintain airborne concentrations below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Skin protection: Chemical resistant, impermeable gloves.

Item No. : 30534

Product name: Thread Sealant with PTFE

Eye/face protection: Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste
Color: White
Odor: Alcoholic
Vapor pressure: 33 mmHg @20°C (68° F)
pH: Not applicable
Boiling point/range: 82.2°C (180°F)
Melting point/range: Not determined
Specific gravity: 1.12 at 25°C (77°F)
Vapor density: 2.07
Evaporation rate: 7.7 (Ether = 1)
Solubility in water: Partial
Partition coefficient (n-octanol/water): Not determined
VOC content: 35.9782%; 343.4283 grams/liter

10. STABILITY AND REACTIVITY

Stability: Stable.
Hazardous polymerization: Will not occur.
Hazardous decomposition products: Toxic fluorides.
Incompatibility: Oxidizing agents.
Conditions to avoid: Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Isopropyl alcohol 67-63-0	No	No	No
Talc 14807-96-6	No	No	No
Castor Oil	No	No	No
Vinyl terpolymer 27360-07-2	No	No	No
Titanium dioxide 13463-67-7	No	No	No
Poly(tetrafluoroethylene) 9002-84-0	No	No	No
Silica, quartz 14808-60-7	Known Carcinogen	Group 1	Yes

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Isopropyl alcohol 67-63-0	Allergen, Blood, Central nervous system, Irritant, Kidney, Liver, Brain, Spleen
Talc 14807-96-6	Some evidence of carcinogenicity, Lung, Irritant
Castor Oil	Irritant
Vinyl terpolymer 27360-07-2	No data
Titanium dioxide 13463-67-7	Irritant, Respiratory
Poly(tetrafluoroethylene) 9002-84-0	No Target Organs
Silica, quartz 14808-60-7	Some evidence of carcinogenicity, Lung, Immune system

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with Federal, State and local regulations.

EPA hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

The shipping classifications in this section are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: RESIN SOLUTION
Hazard class or division: 3
Identification number: UN 1866
Packing group: III
Exceptions: Consumer Commodity ORM-D (Not more than 5L)

International Air Transportation (ICAO/IATA):

Proper shipping name: RESIN SOLUTION
Hazard class or division: 3
Identification number: UN1866
Packing group: III
Exceptions: Consumer Commodity, ID 8000, Class 9 (Not more than 500 ml)

Water Transportation (IMO/IMDG):

Proper shipping name: RESIN SOLUTION
Hazard class or division: 3
Identification number: UN 1866
Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: Not available

CERCLA/SARA Section 302 EHS: None above reporting de minimus.
CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard, Fire
CERCLA/SARA 313: None above reporting de minimus.

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.
WHMIS hazard class: B.2, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 9

Prepared by: Dan Shaw, Product Safety and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.